## User guide for NCLscripts

- timeseries.nc/ draws NCL line plots of time series with netCDF data produced by PALM
- prompt to run the script:

ncl timeseries.ncl [ parameter\_value=value ] [ 'parameter\_string="string" ' ]

- profiles.nc/ draws NCL line plots of profiles with netCDF data produced by PALM
- prompt to run the script:

ncl profiles.ncl | parameter value=value | | 'parameter string="string" |

- cross\_sections.nc/ draws NCL contour plots from two-dimensional cross-sections of NetCDF d ata produced by PALM; instantaneous or time-averaged xy-, xz-, yz- or 3D-data can be used
- possibility of overlaying a vector plot of a 2-dimensional vector
- by default, all time steps, variables and layers in the netCDF data file will be drawn
- prompt to run the script:

ncl cross sections.ncl [ parameter value=value ] [ 'parameter string="string" ' ]

parameter list:

parameter_value/ 'parameter_string'		used by	default	meaning
'file_in'	required	all		netcdf file for input [e.g. "path/name.nc"]
'format_out'	optional	all	"x11"	format of output file [NCGM file ("ncgm"), PostScript file ("ps", "eps", or "epsi"), PDF file ("pdf") or X11 window ("x11") ]
'file_out'	optional	all	"test"	name and location for output file [e.g. "path/name"]
start_time_step	optional	all	1	first time step of plot
end_time_step	optional	all	last time step of input file	last time step of plot
no_columns	optional	all	1	number of plots in one row
no_lines	optional	all	2	number of plots on one sheet
'var'	optional	all	all variables will be plotted	name of variables that shall be plotted [e.g. "ws2, pt,"]; please be sure to have one comma after every variable name (also after the last one!)
combine	optional	profile	0	plot with more than one variable will be switched on [1] or off [0]

parameter_value/ 'parameter_string'		used by	default	meaning
number_comb	required if combine =1	profile	0	number of variables that shall be plotted together in one plot
'c_var'	required if combine =1	profile		name of variables that shall be plotted together in one plot [e.g. "umax,vmax,"]; please be sure to have one comma after every variable name (also after the last one!)
dash	optional	profile	0	use of different line patterns [1] or continuous lines for all time steps [0]
black	optional	profile	0	colored [0] or black and white [1] plots
min_z	optional	profile	0	minimum height of profiles
max_z	optional	profile	maximum height	maximum height of profiles
'sort'	optional	cross	"time"	defines the sequence of plots; either by time step ["time"] or by layer ["layer"]
'mode'	optional	cross	"Fill"	areas between contour levels will be filled with colors ["Fill"], will not be filled but lines will be drawn ["Line"] or will be filled and lines will be drawn ["Both"]
'fill_mode'	optional	cross	"AreaFill"	Style of filling the contour plots ["AreaFill"],["RasterFill"] or ["CellFill"]
shape	optional	cross	1	aspect ratio of axis will be kept [1] or not [0]
хус	required [one (only one!) of these parameters	cross	0	ouput of xy-cross sections will be switched on [1] or off [0]
XZC		cross	0	ouput of xz-cross sections will be switched on [1] or off [0]
yzc	must be set to 1]	cross	0	ouput of yz-cross sections will be switched on [1] or off [0]
xs	optional	cross	0	index of range start for x-coordinate
xe	optional	cross	dimensionsi ze -1	index of range end for x-coordinate
ys	optional	cross	0	index of range start for y-coordinate
ye	optional	cross	dimensionsi ze -1	index of range end for y-coordinate
ZS	optional	cross	0	index of range start for z-coordinate
ze	optional	cross	dimensionsi ze -1	index of range end for z-coordinate

parameter_value/ 'parameter_string'		used by	default	meaning
vector	optional	cross	0	vector plot will be switched on [1] or off [0]
'vec1'	required if vector = 1	cross	"vec1"	name of variable for first component of vector for vector plot [e.g. "u,"]; please be sure to have one comma after every variable name (also after the last one!)
'vec2'	required if vector = 1	cross	"vec2"	name of variable for second component of vector for vector plot [e.g. "v,"]; please be sure to have one comma after every variable name (also after the last one!)
'plotvec'	required if vector = 1	cross	"plotvec"	variables where a vector plot shall overlay [e.g. "u,v,"]; please be sure to have one comma after every variable name (also after the last one!)
ref mag	optional	cross	0.05	value of referenced vector with defined length [can be seen in legend]

- instead of running the prompt with all parameters they can be written into the ascii file .ncl\_preferences which will be read by the script; values/strings given in the prompt overwrite the list values/strings
- .ncl\_preferences runs for all three scripts, so some parameters will be ignored by the scripts and you don't need to consider them
- please be sure to copy the list from the subversion directory into your \$home directory
- please check your strings and values in .ncl\_preferences for correctness if the program aborts
  (it should not abort, if you use the original list with the default values); small differences may let
  abort the program (e.g. there must not be any blanks after the parameter strings); please be
  sure not to swap any rows in .ncl\_preferences